

FOOTING, FOUNDATION REBAR INSPECTIONS WILL BE REQUIRED ON ALL ONE-FAMILY AND TWO-FAMILY HOMES

The Town of Pelham is now under the 2018 International Building Code

Prior to submitting a Building Permit application, the applicant is required to submit (4) four sets of plans to the **Fire Department** for their review and approval stamp. One stamped set of plans will remain at the Fire Department, one stamped set will remain with the applicant, **TWO** stamped sets shall be submitted with the Building Permit application for the Building Inspector's notes, if any. When the permit is approved and the applicant comes in to pick it up, one of the stamped sets will be returned to the applicant and **that set is to stay on site for the Building Inspector to review during inspections.** Any addendums to the drawings through the course of the construction will need to be submitted for approval by the Fire Department and the Building Department.

A State approved septic design with Construction Approval must be submitted for new dwellings.

Per the Planning Board an acceptable Sustained Yield Report from the well driller must be submitted **PRIOR** to issuance of a Foundation or Building Permit.

** Building permits are issued in two phases, Foundation Permit & Building Permit

<u>Foundation Permit</u>. After the permit is issued and after installation, inspections and final approval, the applicant will be required to submit the following in order to obtain the 2nd phase Building Permit:

a. Certified Plot Plan, stamped by a NH Licensed Land Surveyor, that shows the existing foundation with the setbacks to the property lines (does not need to show monuments set at this time).

<u>Building Permit:</u> Once the 2 criteria above are received and deemed acceptable, and all permit and impact fees are paid, the building permit will be issued for the remainder of construction.

Prior to the issuance of a Certificate of Occupancy, a Certified Plot Plan <u>showing monuments</u> set is required, in addition to the items listed in this packet.

ADVANCE PIPELINE NOTIFICATION

1.) Per RSA 674:75 Advanced Pipeline Notification, any new residential development that is located in whole or in part within 1000' of the center point of a natural gas transmission pipeline shall notify the operator of the pipeline of their planned development. Go to pelhamweb.com, then go to the Planning Department and click on the link: Property-Nashua Regional Planning Commission-MapGeo. Put your property address in the search bar, if it shows a red and blue dotted line and you are within the blue dotted line the best way to comply with this new rule is to send an email along MapGeo with the address and screen shot of your search KMEncroachmentsNorth@kindermorgan.com they will respond with guidance for your project. Submit their response with your application.



Town of Pelham 6 Village Green Pelham, NH 03076-3723 APPLICATION FOR BUILDING PERMIT

(603) 635-7811

		Street Locat	ion			
	BUILDING	Subdivision			Map	Lot
		☐ Convention	nal Subdivision Co	onservation Subdivision	Senior Hou	sing Project
2.	TYPE OF IMROVEMENT 1 □ New Building	NT 3.	PROPOSED USE Residential			
	2 Foundation ONLY		1		Deck Pool Wood/Pellet Stove Certificate of Occu Other (specify in so	ipancy
4.	ESTIMATED COST	5.	DESCRIPTION			
	1 Electrical \$					
	2 Plumbing \$					
	3 Mechanical \$					
	4 Other \$					
	Total Cost \$		**Is your property located	within 1000' of the pipelir	ne, (see item #1/front	page)?
6.	7. Will the proposed structure meet current set back & lot size requirements?				Setback ROPERTY LINES** es	
Has			• Is a variance required? [Has a variance been approv Date of Hearing:	ed? 🗌 Yes 🔲 No		-
10	PRINCIPAL TYPE OF I	HEATING FUI	EL 11. DIMENS	IONS		R OF OFF-STREET
1			1 Number of 2 Total Livin 3 Foundation	g Area SF	1 Enclose 2 Outdoor	
13. RESIDENTIAL BUILDINGS ONLY 14. Is the proposed work within 250 ft. of Beaver Brook Island, Gumpas, Long or Harris Ponds: Yes						
	1 Total Bedrooms: Finish	ed	Unfinished		<u> </u>	HDES? Yes No
2 Total Bathrooms: Full1/23/4			(Evidence of approv		pplication OR written	

15. IDENTIFICA		MAILING ADDRESS	DHONE MIMBED			
1. Owner	NAME	MAILING ADDRESS	PHONE NUMBER			
2. General Contractor						
3. Electrician**						
4. Plumber**						
SIGNATURE OF	OWNER	APPLICATION I	DATE:			
ELECTRIC	CAL & PLUMBING WORK REQUIRE	SEPARATE PERMITS – THEY ARE NOT INCLUDE TRUCTION PLANS ARE NOT TO EXCEED 11"X 1".	DED IN THE BUILDING PERMIT			
********		FENT USE ONLY – DO NOT WRITE BELOW THIS				
Zoning/Planning	Compliance					
APPROVED						
Conditions of Ap	proval to be noted on Building F	ermit:				
DENIED						
Reasons for Deni	ial: <u>See ADMINISTRATIVE DE</u>	CISION DATED:				
Jenn Beauregard	Jenn Beauregard, Planning Director / Zoning Administrator Date					
Building Code C	<u>ompliance</u>					
APPROVED [
Conditions of Ap	proval to be noted on Building F	ermit:				
BUILDING PERMIT	Г FEE:	-	1			
Roland Soucy, B	uilding Inspector	Date				

New Hampshire Residential Energy Code Application

for Certification of Compliance for New Construction, Additions and/or Renovations of Detached One- and Two-family dwellings and multi-family dwellings (townhouses) not over 3 stories

EC-1 Form

Minimum Provisions from 2018 IRC Chapter 11 Effective Date: July 1, 2022

Owner/Owner I	Owner/Owner Builder: Company Name: (if applicable)			Or: Company Nam	n <mark>e</mark> :	
Name:	Name:			Name:		
Mail Address:	Mail Address:					
Town/City:	Town/City: State: Zip:		Town/City:	State:	<mark>Zip:</mark>	
Phone:	Cell:		Phone:	Cell:		
E-Mail:	E-Mail:			1		
Location of Pro	posed Structi	ıre:	Type of Construc	tion:		
Tax Map #:	Lot		Residential	O Small Cor	<u>mmercial</u>	
Ctroot			O New Building O	Renovation	O Addition	
<mark>Street:</mark>			O Thermally Isolate			
			O Modular Home: tl			
Town/City:	County:		this form detailing supplementary rooms and Floor and/or		and Floor	
			Basement insulation unl	ess the floor insul	ation is installed	
			or provided by the manu	ufacturer and no l	neated space is	
7000 F O Obs. 11	Zono F			added. Total New Conditioned* Floor Area:		
Zone 5 Cheshire, Hillsborough, Rockingham Strafford			Total New Condi	itionea* Floa	or Area:	
Zone 6 O All other	Zone 6 All other NH counties and town of Durham			ft²		
ZONE AN COUNTRY COUNTR			Basement or Craw space is one being heated/ or w/ a fixed opening into o insulated) Conditioned? O No Full Basement Slab on Grade	cooled, containing conditioned space.	uninsulated ducts Walls must be ust be insulated)	
Structure is EX	(EMPT because:		Form Submitted by:			
☐ Mobile Home	On an histor	ic register	☐ Owner ☐ Builder	Other		
			e and correct, and constructio unicipal code official or New			
<mark>ignature</mark>		Print Nam	<u>e</u>		Date	
Official Use Only						
Date Complete Applic	cation Received:		Approved by:	Date:		
Approval Number:			Stamp:			

Directions: Complete the "Your Proposed Structure" columns. No measurements or calculations are needed. Copies of plans are NOT needed. If you at least meet the Energy Code requirements, your project will be approved. Write N/A in any section that does not apply to your project. If your planned structure does meet these requirements, consider downloading REScheck

http://www.energycodes.gov/rescheck to explore energy modelling options. Please submit pages 1 and 2 only.


	1 52	YOUR PROPOSED STRUCTURE		UR PROPOSED STRUCTURE
Building Section	Required R or U Values		Write Planned R and U Values	Brands / Models / insulation type and thickness (if known)
Window U Factor (lower U is better)	U .30 (maximum) U32 (if log walls in Zone 5 U30 (if log walls in Zone 6 U .45 (Thermally Isolated Sunroom)	Write in U-Value	Check if Sunroom Log Walls
Skylights	U .55 (or less) U .70 (Thermally Isolated Sunroom	ns only)		
Flat Ceiling ⁱ or	Truss Energy	ed Heel or by Truss	Write in R-Value	NOTE: R-38 will satisfy the requirement for R-49 if the full R-38 insulation value is maintained over the outside plates. If using only R-38 (Zone 5 or 6), you must certify that you will maintain R-38 over the plates by checking the box below.
Flat Ceiling with Raised or Energy Trusses R-value	R-49 (Zone 5 or 6) if using the above construction technique R-49 if log walls R-49 (Zone 5 or 6) if maintai the full R va over the pla	ning Iue tes	If using only R- 38 in Zone 5 or 6 you must check this box	By checking this box, I certify that this structure is being built with a raised energy truss or that the full R-value of the ceiling insulation will be maintained over the outside plates.
Sloped or Cathedral Ceiling	R-30 (Zone 5 & 6) if less than 500 ft sq or 20% of total ceiling area or as above R-24 (Thermally Isolated Sunrooms only)		Write in R-Value	Check if ☐ Sunroom
Above Grade Wall ⁱⁱ R-value	R-20 R-20 plus R-5 Cavity Insulation only or Insulation or R-13 plus R-5 Cavity plus Continuous Insulation R-13 (Thermally Isolated Sunrooms only) R-13 (Thermally Isolated Sunrooms only)	Cavity uous n R-10 us sulation nally	Write in R-Value	Log homes must comply with ICC400-2012, have an average minimum wall thickness of 5" or greater with specific gravity of ≤0.5 or 7" with specific gravity >0.5. Check if Sunroom Log Walls
Door U-Value	U .30 (maximum)		Write in U-Value	One opaque door in the thermal envelope is exempt from the U-factor requirement.
Floor R Value (e.g., floor over Basement or garage)	R-30 or Insulation sufficient to fill joist cavity minimum R-19 For both Zone 5 and Zone 6 R-19 Cavity Insulation or R-15 Continuous Insulation		Write in R-Value	If conditioning the basement you must insulate Basement Walls . If not, you may
Basement or Crawl Space Wall R Value			Write in R-Value	insulate either Floor or Basement Wall s and Slab Edge (if ≤ 1' of grade)


Slab Edge ⁱⁱⁱ R Value	R-10 2' (Zone 5) 4' (Zone 6) (see drawing pg 3) add R-5 if the Slab is heated or R-15 under entire heated slab if a log home.	Write in R-Value	Check if Heated Slab
Air Sealing	A blower door test is required . The test must demonstrate an air exchange rate of three Air Changes per Hour (ACH) or less @ 50 Pa.	Blower Door	If required by the code official, an approved third party may be required to conduct the blower door test.

Submit pages 1 and 2 to local municipal code official or NH Department of Energy at energy.nh.gov
Phone: 603.271.3670 Fax: 603.271.3878

2015 Footnotes to Residential Energy Code Application for Certification of Compliance

ⁱ <u>Ceilings with attic spaces</u>: R-38 in Zone 5 or 6 will be deemed to satisfy the requirement for R-49 wherever the full height of uncompressed R-38 insulation extends over the wall top plate at the eaves or the full R-value is maintained. This is often accomplished by using a raised heel or energy truss as shown in the diagram below or by using higher R-value insulation over the plates.






- ii R-20 + R-5 means R-20 cavity insulation plus R-5 continuous insulation. If structural sheathing covers 25 percent or less of the exterior, R-5 sheathing is not required where the structural sheathing is placed. If structural sheathing covers more than 25 percent of exterior, the structural sheathing must be supplemented with insulated sheathing of at least R-2.
- iii Slab edge insulation must start at the top of the slab edge and extend a total of two (Zone 5) or four feet (Zone 6). Insulation may go straight down, out at an angle away from the building, or along the slab edge and then under the slab. A slab is a concrete floor within 1' of grade level. See diagram below.

The top edge of insulation installed between the exterior wall and the interior slab may be mitered at a 45 degree angle away from the exterior wall.

Allowable Slab Insulation Configurations



A or A+ B must equal two feet in Zone 5 or four feet in Zone 6

MODULAR HOMES must be certified by the NH Department of Safety. Unless the floor insulation is provided by the manufacturer this form may be submitted. This form may also be submitted if the basement is to be insulated or supplementary heated space is added to the home upon or after it is set.

2018 International Residential Code (IRC) effective July 1, 2022 Residential Energy Code Requirements IRC Chapter 11 The following list is intended as a general summary of energy related requirements. Please consult the 2018 IRC Chapter 11 for complete requirements.

Air Leakage Code Section N1102.4		The building thermal envelope shall be constructed to limit air leakage in accordance with the requirements of IRC Sections R1102.4.1 through R1102.4.4. The building thermal envelope must be durably sealed to limit infiltration. See Table N1102.4.1.1 for a list of thermal envelope elements and installation criteria.
		Building envelope air tightness shall be verified to comply by Blower Door testing to not exceed air leakage of 3 Air Changes per Hour (ACH) at 50 Pascals pressure. The local Building Official may require an independent 3 rd party to conduct the test.
	Testing Code Section N1102.4.1.2	The Blower Door Test is the required method to demonstrate code compliance with the air leakage requirement. Blower Door Test conducted by:
	Fireplaces Code Section N1102.4.2	New wood-burning fireplaces shall have tight-fitting flue dampers or doors and outdoor combustion air.
	Recessed Lighting Code Section N1102.4.5	Recessed lights in the thermal envelope must be type IC rated and labeled as meeting ASTM E 283 and sealed with a gasket or caulk between the housing and the interior wall or ceiling covering.
	High-Efficacy Lighting Code Section N1104.1	Not less than 90 percent of the lamps in permanently installing lighting fixtures shall be higherflicacy lamps or not less than 75 percent of the permanently installed lighting fixtures shall contain only high-efficacy lamps.
	Materials and Insulation Identification Code Section N1101.5 and N1101.10	Materials, systems and equipment shall be identified in a manner that will allow a determination of code compliance. Manufacturer manuals for all installed heating, cooling and service water heating equipment must be provided. Insulation R-values, glazing and door U-values and heating and cooling equipment efficiency must be clearly marked on the building plans, drawings or specifications.
	Pull-Down Attic Stairs, Attic Hatch, and Knee Wall Doors	Should be insulated to a level equal to the surrounding surfaces and tightly sealed and weather-stripped at the opening.
	Code Section N1102.2.4	
	Full size Attic or Basement Entry Doors Code Section N1102.3.4	All doors leading from a conditioned space into an unconditioned attic or enclosed attic or basement stairwell should be insulated and weather-stripped exterior rated door units meeting the U-factor requirement. One door is exempt.
	Duct Insulation Code Section N1103.3.1	Supply and return ducts in attics must be insulated to at least R-8 where 3 in. diameter or greater and not less than R-6 for ducts smaller than 3 in. diameter Supply and return ducts in other portions of the building must be insulated to at least R-6 where 3 in. diameter or greater and not less than R-4.2 for ducts smaller than 3 in. diameter. Exception: Ducts or portions thereof located completely inside the building thermal envelope.

	_	
Duct Construction Code Sections N1103.3.2 and N1103.3.5	Ducts, air handlers and filter boxes shall be sealed. Joints and seams must comply with the <i>Int. Mech. Code</i> or Section M1601.4.1 of the <i>International Residential Code</i> . Building framing cavities shall not be used as ducts or plenums (neither supply nor return).	
Duct Testing Code Sections 1103.3.3	Ducts shall be pressure tested to determine air leakage by either 1) rough-in test or 2) post-construction test. Rough in Test: Ducts must be no leakier than 4 CFM per 100 sqft of conditioned floor area with air handler installed or 3 CFM per 100sqft without the air handler installed. Post Construction: Ducts must be no leakier than 4 CFM per 100 sqft of conditioned floor area. See Code for further requirement details.	
	Test conducted by:	
	Duct test result at 25 Pa:Post construction orRough-in test	
Town water Controls	At least one thermostat must be provided for each separate heating and cooling system. The thermostat controlling the primary system must be equipped with a programmable thermostat.	
Temperature Controls Code Section N1103.1&1.1	tech. Code or Section M1601.4.1 of the International Residential Code. Building framing avities shall not be used as ducts or plenums (neither supply nor return). The stable of the supply nor return is a suited by the building framing avities shall not be used as ducts or plenums (neither supply nor return). The stabled person of the supply nor return is a suited by the suited supply nor return). The stabled person of the supply nor return is a suited by the suited by th	
Mechanical System Piping Insulation Code Section 1103.4	Mechanical system piping capable of conveying fluids at temperatures above 105°F or below 55°F must be insulated to R-3.	
Circulating Hot Water Systems Code Section N1103.5	Controls for circulating hot water system pumps shall start based on the identification of a demand for hot water within the occupancy. The controls shall automatically turn off the pump when the water in the circulation loop is at the desired temperature and when there is no demand for hot water.	
	Circulating domestic hot water system piping shall be insulated to R-3.	
Mechanical Ventilation Code Section N1103.6	The building shall be provided with ventilation that meets the requirements of Section M1507 of this code or the International Mechanical Code, as applicable, or with other approved means of ventilation. Outdoor air intakes and exhausts must have automatic or gravity dampers that close when the ventilation system is not operating.	
Equipment Sizing Code Section N1103.7	Heating and cooling equipment shall be sized in accordance with ACCA Manual J or other approved heating and cooling calculation methodologies. Equipment shall have an efficiency rating equal to or greater than applicable federal standards.	
Certificate Code Section N1101.14	A permanent certificate, completed by the builder or registered design professional, must be posted on or in the electrical distribution panel. It must list the R-values of insulation installed in or on the ceiling, walls, foundation, and ducts outside the conditioned spaces; U-factors and SHGC for fenestration. The certificate must also list the type and efficiency of heating, cooling and service water heating equipment.	
Existing Buildings and Structures See Appendix J of IRC	The purpose of these provisions is to encourage continued use of existing buildings and structures. Work in existing buildings shall be classified into categories of repair, renovation, alteration and reconstruction. Consult this Appendix for specific requirements related to work in existing buildings.	



Proposed Location:

APPLICATION FOR DRIVEWAY PERMIT

Pursuant to the provisions of RSA 249:17, RSA 236:13 and the Subdivision Regulations of the Town of Pelham, New Hampshire, permission is requested to install a driveway entrance to my property at a location which will meet the requirements for safety specified in said statutes and regulations.

Attention: The Planning Department, Highway Department, and Fire Department **must** be provided an approved septic plan showing the proposed location and profile of the driveway prior to inspections or construction, see below for details.

·						
Tax Map Number of F	Tax Map Number of Property:					
Street Name:		House #				
Side of Street:	Side of Street:					
	(North, East, South, West)					
Driveway to Serve	Single Family Dwelling	Industry				

As the landowner / applicant, I hereby agree:

- 1. To construct the driveway entrance only for the bona fide purpose of securing access to private property such that the roadway right-of-way is used for no purpose other than travel.
- 2. To construct the driveway entrance at the location determined by the Pelham Planning Board or its duly authorized agent to be the safest and according to the conditions imposed by the aforesaid statutes and regulations.
- 3. To furnish and install, at the applicant's expense, drainage structures that are necessary to maintain existing roadway drainage and adequately handle increased runoff resulting from present and future development.
- 4. To hold harmless the Pelham Planning Board and its duly authorized agents and employees against any action for personal injury and/or property damaged sustained by reason of the exercise of any driveway permit issued by the Pelham Planning Board or it's duly authorized agents and employees.

Conditions:

- 1. This permit requires the lot frontage area adjacent to the street be graded so that the elevation of the frontage, including driveway, will slope away from the edge of the street no less than 6 feet in width and not less than 6 inches in depth below the elevation of the edge of the street.
- 2. A copy of the plan with the proposed driveway location and profile is to be submitted to the Fire Department for their review and approval. Once approved, plans shall be submitted to both the Planning Department and the Highway Department with the Driveway Permit Application.
- 3. Each driveway is to have a rough inspection performed by the Highway Department prior to Building Permit issuance meaning, it must be roughed in and graded accordingly. In addition, the Highway Department requires a final inspection of the finished paved driveway. The Fire Department will also inspect the final driveway prior to issuance of a Certificate of Occupancy.
- 4. Driveways must have at minimum, 250-feet of all-season safe sight distance when intersecting a Local-1 or Local-2 Street; and 325-feet if intersecting a Collector Street.

- 5. All residential driveways are to intersect the roadway at a ninety-degree angle with an apron no smaller than 14-feet wide and no larger than twenty-feet wide with a negative slope of at-least 2% and at most 3% which is to be maintained for no-less than ten-feet from the edge of roadway. At that point the slope can change, but with an algebraic difference of no more than 10%.
- 6. A culvert, if required, not less than 6 inches in diameter shall be installed under the driveway no less than 18 inches below the surface and in line with the drainage gutter referred to in Condition #1. The soil at each end of the culvert shall be stabilized by a header of adequate design.
- 7. The driveway entrance may be flared as it approaches the roadway.
- 8. Other access to the roadway from the premises is to be prevented by construction of a barrier or barriers, such as a grass plot, low hedge, curbed island, etc. The front face of this barrier shall be no-less-than 25 feet from the centerline of the pavement.
- 9. In most cases the roadway right-of-way line is 25-feet from the parallel to the centerline but should be verified.
- 10. No structures, including buildings, permanent or portable signs, lights, displays, fences, walls, sports equipment, sprinkler systems, etc. shall be permitted on, over, under or in the right-of-way.
- 11. No parking, catering or servicing shall be conducted within the right-of-way.
- 12. No curbing shall be cut. Where there is curbing, the driveway shall be butted up against the curbing.
- 13. Failure (a) to adhere to the standards and engineering drawings, if any, previously submitted; (b) to adhere to the terms and conditions of the Driveway Permit Application: (c) to adhere to the terms of this permit; (d) to adhere to RSA 249:17 and the Driveway Permit Regulations of the Town of Pelham; and (e) to complete the driveway facility within one year, shall render this permit null and void.

The Highway Safety Committee recommendation & Fire Chief approval must be granted prior to issuance of Certificate of Occupancy.

Printed Name of Landowner	Signature of Landowner				
Owners Phone Number					
ALL REQUESTS FOR DRIVEWAY INSPECTIONS SHOULD BE CALLED IN TO 603-635-7811. PLEASE ALLOW ONE WEEK FOR EACH INSPECTION.					
DO NOT WRITE BEL	OW THIS LINE. FOR OFFICE USE ONLY				
☐ DRIVEWAY PERMIT APPROVED	☐ DRIVEWAY PERMIT DENIED				
If Driveway denied, why?					
Rough Driveway Inspection Highway Dept. Road Agent:					
Final Driveway Inspection Highway Dept. Road Agent:					

The following driveway specifications are excerpted from the Town of Pelham Subdivision Regulations and are provided for your reference, Appendix 1 – Roadway Design, Section L, as follows:

L. Driveways and Other Accesses for Single Family and Duplex lots

Driveways and other accesses to the local street network or proposed streets shall be constructed in accordance with the relevant provisions of the Pelham Subdivision Regulations, and the most recent version of the document entitled "State of New Hampshire Department of Transportation Policy and Procedure for Driveways and Other Accesses to the State Highway System". Driveways shall be defined in accordance with the definitions given in the most recent version of the Institute of Transportation Engineers Guidelines for Driveway Design and Location. Both of these documents are hereby incorporated into these regulations by reference. The more stringent requirements of the Pelham Subdivision regulations shall apply where different. The Planning Board shall retain approval authority for all wetland or WCD crossings or other lot access where steep slopes or other special features are present.

All driveways and other lot accesses shall be constructed as permitted then approved by the Fire Chief as the Authority Having Jurisdiction (AHJ) in accordance with NFPA I and in conjunction with Highway Safety Committee review and guidance prior to issuance of a building permit. The Fire Chief or his agent shall have jurisdiction for the design and location of all dry hydrants, fire cisterns or other water access.

A Special Permit will be required by the Planning Board before a driveway approved under these regulations is relocated with review and comment by the Highway Safety Committee and approval by the Fire Chief or his agent prior to the issuance of a building permit.

Driveway Specifications:

- 1. Driveways shall meet the roadway at a perpendicular angle and shall be flared 2 feet on each side where it meets the roadway. The driveway shall have a maximum slope of +/- 5% for the first 20 feet and any curves in the driveway shall have a minimum radius of 25' at the inside of the curve and 50' at the outside curb line.
- 2. Driveways of 150' or less in length shall be a minimum of 12' in width with a maximum slope of +/- 10% after the first 20' and the alignment shall permit a WB-50 Vehicle to pass (standard fire truck).
- 3. All driveways between 150' and 300' shall be a minimum of 14' in width with a maximum slope of +/- 10% after the first 20'.
- 4. All driveways exceeding 300' in length shall be a minimum of 14' in width after the first 20' with a maximum slope of +/- 10% and must be terminated with a paved turn-around area adequate for a WB/50 vehicle with a maximum slope of +/- 5% within the turn-around area.
- 5. All driveways 500' or more in length shall be a minimum of 14' in width, with a maximum slope of +/- 10% after the first 20' and shall include a pull over at the midpoint to accommodate a WB/50 vehicle allowing another WB/50 vehicle to safely pass. Driveways of this length shall be terminated with a paved turn-around area adequate for a WB/50 vehicle with a maximum slope of +/- 5% within the turn-around area.
- 6. All New subdivisions shall submit plans showing proposed driveways conforming to these minimum standards of this section in order to be approved.
- 7. Whenever a building permit is pulled the applicant shall submit a driveway application with a certified driveway plan that either conforms to the subdivision plan approved under these standards, or they must seek a special permit from the Planning Board and prove a new location of their choosing meets these minimum standards. Verification that the driveway complies with this section shall be made in writing by the Planning Board's review engineering firm.
- 8. All private driveways serving Senior and Elderly Housing projects shall be constructed to Town Road Specifications as defined within this document in addition to meeting all the requirements of the Fire Chief under NFPA I as described in this section



(wood being used for personal use).

WAIVER OF INTENT TO CUT WOOD OR TIMBER NOTICE

Effective January 1, 1999 Pursuant to changes in RSA 79:1 II b Owners cutting for land conversion purposes are subject to the following condition:

- (b) The following persons **shall not** be required to file an intent to cut or be subject to the tax imposed by this Chapter:
 - (5) A person who cuts or causes to be cut, within the tax year, up to 10,000 board feet of logs and 20 cords of wood or the equivalent in whole tree chips, from the person's own land within a municipality, for land forest uses, provided that those persons intending to convert the use of the land have secured all required permits, including, but not limited to, building permits, subdivision or zoning permits, excavation permits or site plan approvals, as necessary for the use to which the land will be converted, and are able to furnish proof of such permits.

l.	(Owner/Bu	uilder) do hereby certify that I have refused an Intent to	
Cut for the property lo		,,,	
signing this form, I am RSA 79: 1 II (b) (2) (s cutting operation before appropriate notice of its officials shall constitute post the certificate on I certify that I have reasoned.	a certifying that no standing ee above) in preparation re the appropriate notice intent has been filed with the a violation by the owne the job in a conspicuous and and understand the ab	on the Pelham tax maps. I understand that by ag timber will be cut on this property except as defined in for building a house. I also understand that "starting a of intent has been filed with the Town and signed by the Town and signed by the Town and signed by the appropriate municipal or or any other person doing the cutting or both. Failure to place upon receipt shall constitute a violation." ove form. If I need further information concerning Intented any requested information form the Pelham Assessor's	
		Owner / Builder	
		Date	
I certify	that there is no wood be	ng cut on this property	
Lcertify	that there is wood being	cut, but it is exempt per the above mentioned RSA	

How to Obtain Permits to Install Oil or Gas Burning Equipment

- 1. Applicant must fill out an application for permit to install oil burning equipment **or** gas burning equipment through the Fire Department.
- 2. Application fee is \$25.00 which is paid to the Fire Department.
- 3. The completed application will be held until the Fire Department is informed by the applicant that the burner is ready for inspection. At that time, an appointment will be made for the fire inspector to inspect the burner.
- 4. At the time of inspection, the fire inspector will also be checking your smoke alarms (hard-wired for new construction; battery operated for older homes), your battery operated or plug-in carbon monoxide detector alarms and making sure the number of your house is visible from the road.
- 5. Once inspected and approved, the applicant will be given (or mailed) a signed copy of the Permit,
- 6. Signed permit should be given to the Planning Department

Laws and regulations governing the installation of oil burners, gas burners, tanks, piping, etc. may be found in the National Fire Protection Association (NFPA) Standards and Town of Pelham guidelines.

If you have any further questions on the above procedures, please contact the Fire Department secretary at 635-2703, Monday thru Friday, 8:30 am to 4:30 pm.

PROPANE/OIL PERMITS AND INSPECTIONS

		FIRE DEPARTMENT		
DEVICE	PLUMBING PERMIT	GAS PERMIT	ELECTRIC PERMIT	FIRE DEPT. PERMIT
Propane Tank/Piping				
(Street Side of Regulator)				•
Propane Tank/Piping				
(House Side of Regulator		•		
Oil Burner (Forced Hot Air)			•	•
Oil Burner (Forced Hot Water)	•		•	•
Propane (Forced Hot Air)		•	•	•
Propane (Forced Hot Water)		•	•	•
Oil Hot Water Heater	•		•	•
Propane Hot Water Heater	•	•	•	
Propane Generator			•	•
Gas/Diesel Generator			•	•

PERMITS TO BE PULLED BEFORE ANY WORK IS INITIATED

This Policy Established On September 12, 2013 By Order Of The Pelham Fire Chief & Planning Director

James Midgley, Fire Chief

Jeff Goward Planning Director

OCCUPANC	1 I ERWIII CHECKLISI
LOCATION:	MAP: LOT:
Any permit to occupy a residential or commercial	building requires the following:
1. Final Building Inspection	
2. Final Electrical Inspection	
3. Final Plumbing Inspection	
4. Final Driveway Inspection (Highway Safety	Committee 635-7811)
The following information must accompany this fo	orm or be on file at the Planning Dept.:
Certified Plot Plan showing location of build	ing & monuments set (granite bounds, iron pipes)
Copy of Septic As-Built Plan & Operation A Control Commission must accompany this for	Approval from New Hampshire Water Supply and Pollution m
Photo confirmation or letter stating WCD Sign	ns have been posted, if applicable.
Oil/Gas Burning Permit (from the Fire Depa	rtment 635-2703)
of Health Water Supply Regulations – Well O	ied Well Testing Lab in accordance with Section 5 of the Board rdinance. If any primary elements fail, a point of entry mitigation e installer is required (invoices are not acceptable). Post treatment test
A completed Well Data Report submitted by	the well driller or his agent.
A completed Blower Door Test . Must demons (ACH) or less @ 50 Pa.	strate an air exchange rate of seven Air Changes per Hour
☐ A COPY OF THE BUILDING PERMIT IN INSPECTIONS	ICLUDING ALL SIGNATURES/DATES OF
All necessary approvals must be submitted to the requesting an occupancy permit. NO EXCEPTIO	ne Planning Department at least 3 business days in advance of DNS!!!!
I hereby certify that all the above approvals have above.	been submitted to the Planning Department in accordance with
Printed name of Builder/Owner:	Phone #
Signature of Builder/Owner:	Date:

Please do not submit this with your application.

Keep this form to complete & submit at time of Certificate of Occupancy request.